

# METAL BUILDING ROOF CURB (SINGLE) - ORDER FORM

## STANDARD FEATURES

1. 18 Ga. AZ55 galvalume steel
2. Corners mitered & welded watertight
3. Curb welds primed after fabrication
4. Water cricket
5. 8" minimum height
6. Includes gasket & mastic
7. Internal angle reinforcing
8. 1 1/2" thick - 3# density fiberglass insulation

## OPTIONS

1. \_\_\_\_\_
2. \_\_\_\_\_
3. \_\_\_\_\_
4. \_\_\_\_\_
5. \_\_\_\_\_

## PROJECT DETAILS

PROJECT NAME: \_\_\_\_\_  
 \_\_\_\_\_  
 SITE ADDRESS: \_\_\_\_\_  
 \_\_\_\_\_  
 CITY: \_\_\_\_\_  
 STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_  
 JOB NUMBER: \_\_\_\_\_

**Dimensions:**  
 O.D. Length - "L"  
 I.D. Length  
 O.D. Length - "W"  
 I.D. Length  
 11" (flange width)  
 5" (flange thickness)  
 4" (flange offset)  
 4" (flange offset)  
 Min. Height - "R"  
 8" Std. (flange height)  
 4" (flange offset)  
 Slope Per 12"  
 Max Height

**Details:**  
 All angles on 24" centers  
 Under-Over Only  
 Notch Detail A (Under-Over Only)  
 12" Pitch  
 Roof Pitch? \_\_\_\_\_ :12  
 Rib Style Required?  
 SSR-Style Panel  
 R-Style Panel  
 T-Style Panel\*\*  
 Additional Details Required?  
 Roof Panel Name? \_\_\_\_\_  
 Paint Mfg.? \_\_\_\_\_  
 Paint Color? \_\_\_\_\_  
 Splice? \_\_\_\_\_ Yes \_\_\_\_\_ No  
 Fasteners? \_\_\_\_\_ Yes \_\_\_\_\_ No  
 Caulk? \_\_\_\_\_ Yes \_\_\_\_\_ No

**Loose Ribs?**  
 \_\_\_\_\_ Under/Over  
 \_\_\_\_\_ Over/Over

**Welded Ribs?**  
 \_\_\_\_\_ Under/Over  
 \_\_\_\_\_ Over/Over

\*\*T-Style panels require loose or welded clips on tall side of curb only

QUANTITY	INSIDE DIMENSION "W" x "L"	OUTSIDE DIMENSION "W" x "L"	HEIGHT "R"	TAG
	x	x		
	x	x		
	x	x		
	x	x		
	x	x		



SIGN FOR APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_